ERRATA SHEET FOR THE USER'S MANUAL TO ANSI/ASHRAE STANDARD 62.1-2007 VENTILATION FOR ACCEPTABLE INDOOR AIR QUALITY

October 9, 2009

The corrections listed in this errata sheet apply to all copies of ANSI/ASHRAE Standard 62.1-2007 User's Manual. The first printing has no identification on the outside back cover. The second printing is identified on the outside back cover as "ISBN 978-1-933742-25-0 Product Code: 90157 2/09". In addition, the second printing includes a note at the bottom of the inside cover of the first page that states "*Errata noted in the list dated 06/17/2008 have been corrected.*" The shaded items have been added since the previously published errata sheet dated June 17, 2008 was distributed. Only the shaded items apply to the second printing.

NOTICE: ASHRAE now has a list server for Standing Standards Project Committee 62.1 (SSPC 62.1). Interested parties can now subscribe and unsubscribe to the list server and be automatically notified via e-mail when activities and information related to the Standard is available. To sign up for the list server please visit **Standards List Servers** on the Standards and Codes section of the ASHRAE website at http://www.ashrae.org/publications/detail/15620.

Page Erratum

Preface On page 2 of the **Preface**, under **Official Interpretations**, second paragraph, change the last sentence to read as follows: "See the ASHRAE Web site at http://www.ashrae.org/technology/page/121 for more information on requesting an interpretation.

- 2-1 Spaces Covered (§ 2.1). In the second paragraph change "Standard 62.2-2004" to "Standard 62.2-2007."
- **Example 2-B Retroactive Application of the Standard.** In the question, **Q**, change "ASHRAE *Standard 62.1-2004*" to "ASHRAE *Standard 62.1-2007*". In the answer, **A**, change "*Standard 62.1-2007*" to "*Standard 62.1-2007*".

5-5 Example 5-B Natural Ventilation Prescriptive Requirements.

- 1. Make the following changes to the diagram: Change "3 m² typ. 16" to "3 m² typ. 12" and "1.5 m²" to "1.5 m² typ. 12".
- 2. Make the following corrections to the data table: (Note: Additions are shown in <u>underline</u> and deletions are shown in <u>strikethrough</u>.)

Space No.	Width (m)	Depth (m)	Floor Area (m²)	Gross Window Area (m ²)	Direct Opening Area (m²)	Direct Opening (%)	Meets Direct Criterion?	Indirect Opening Area (m ²)	Indirect Opening Area (%)	Meets Indirect Criterion?	Within 8 m of Opening Wall?	Meets Prescriptive?
1	8	8	<u>64</u> 676	24	4.8	7.5	Y	-	-	N	Y	Y
2	4	4	<u>16</u> 169	6	2.4	15	Y	-	-	N	Y	Y
3	4	4	<u>16169</u>	6	2.4	15	Y	-	-	N	Y	Y
4	5	4	<u>20</u> 208	4.5	1.8	9	Y	i	-	N	Y	Y
5	5	4	<u>20</u> 208	1.5	0.6	3	N	-	-	N	Y	N
6	6	8	<u>48520</u>	12	4.8	10	Y	Ī	-	N	Y	Y
7	12	4	<u>48</u> 507	-	-	-	N	<u>3</u> 32	6.3	N	<u>N</u> ¥	N
8	4	4	<u>16</u> 169	-	-	-	N	<u>3</u> 32	18.8	Y	N	N
9	2	4	<u>8</u> 78	-	-	-	N	<u>3</u> 32	37.5	Y	Y	Y

3. Correct the following notes as shown:

Direct opening area is the area of the operable opening (20% of the gross window area for 3 m^2 windows, 40% of the gross window area for the 1.5 m^2 windows) direct from the room to the outdoors.

Direct opening in percentage is the direct opening areaare divided by the floor area.

- **Example 5-F Dehumidification in Virginia.** At the top of page 5-24, third line, change "*Standard 62.1-2004*" to "*Standard 62.1-2007*". In the table in part II, for Walls, the degree symbol is missing; change to read "82°F[#]".
- **5-36** In the second column on page 5-36 change "ASHRAE *Standard 90.1*" to "ASHRAE/IESNA *Standard 90.1*".
- **8-1 General** (§ **8.1**). In the first sentence of the first paragraph change "*Standard 62.1-2004*" to "*Standard 62.1-2007*".
- **8-2 Example 8-A Milestone Dates.** In the question, **Q**, change "Standard 62.1-2004" to "Standard 62.1-2007".
- **Example 8-1 Wings Constructed in Different Years.** In the first paragraph of answer, **A**, change "Standard 62.1-2004" to "Standard 62.1-2007".